




FLAT CORD Type SPT

Parallel Cord. Speaker Cord. 60°C, 300 Volts



- SPECIFICATIONS** PHILFLEX Type FLAT CORD meets and exceeds applicable UL 62 standard, PNS 163 standard.
- APPLICATION** PHILFLEX Type FLAT CORD conductors are primarily used in small appliances for indoor services rated at 300 Volts AC or below.
- Conductors** Annealed (soft) copper,
- Insulation** Tough and moisture resistant, Polyvinyl Chloride (PVC)
- Color** Black, white, red, blue, yellow, and green.
Speaker Cord available in black/red color coding.
- Sizes** Sizes 0.30mm² through 3.5mm² are available.

Catalog Number	Size / Nom. Area of Cond. mm ²	Approx. Cond. Diameter mm	Approx. Overall Diameter mm		Type	Max. Conductor Resistance @ 20 °C Ohm / km	Approx. Cable Weight kg / km	Standard Length m
			major	minor				
FC 22	0.30	0.70	4.6	2.3	SPT-1	58.80	16.40	150
FC20	0.50	0.93	5.0	2.5	SPT-1	35.25	21.50	150
FC18	0.75	1.10	5.4	2.8	SPT-1	23.52	27.50	150
FC16	1.25	1.50	7.8	3.9	SPT-2	14.11	52.80	150
FC14	2.00	1.80	11.6	5.8	SPT-3	9.14	104.68	150
FC12	3.5	2.40	12.8	6.4	SPT-3	5.20	143.04	150

Lengths other than those specified are available upon request



PHILFLEX®



50 YEARS of QUALITY & EXCELLENCE

No. 1 Wires & Cables Brand

Serving the Local & Global Market
A True Super Brand!

